

ENERGY-ABSORBING FLEXIBLE POLYMER VEHICLE WHEEL

BACKGROUND OF THE INVENTION

1. FIELD OF THE INVENTION

5 The present invention relates to wheels for vehicles. More particularly, the present invention relates to a lightweight, energy-absorbing, flexible vehicle wheel constructed from an injection molded engineered polymer, such as, for example, a toughened nylon reinforced with carbon fibers, glass fibers, or kevlar fibers, wherein the wheel may be embodied in either modular or one-piece construction, and comprises ribs and varying cross-sectional thicknesses for controlling stiffness; O-rings, gaskets, or dynamic u-cup seals for sealing contact surfaces; an alignment mechanism for facilitating bead ring alignment; and a mud plug having a quick release mechanism for quick removal.

2. DESCRIPTION OF THE PRIOR ART

10 It is often desirable to provide a vehicle with lightweight wheels able to withstand substantial and repeated impacts and other operating stresses without significant negative effect or performance degradation. This is true for almost all vehicles, and is particularly true for off-road and off-road racing vehicles that travel over punishingly uneven terrain and that may even become substantially airborne at times, thereafter crashing back to earth. Such conditions and uses, it will be appreciated, subject the wheels to significant stresses.

15 Wheels constructed from both aluminum and steel are well-know in the art. Unfortunately, metal wheels suffer from a number of disadvantages and limitations, including a generally heavier weight and a lack of energy-absorbing flexibility. Aluminum, for example, though a relatively lightweight metal, when used in wheel construction must typically be made undesirably thick and correspondingly heavy to have the strength required to withstand the aforementioned punishing driving conditions. Unfortunately, aluminum has a relatively low yield strength, meaning it is easily permanently deformed. When such deformation occurs, tire leakage or de-beading may result. Those with skill in the arts of off-road travel and off-road racing will appreciate these drawbacks and limitations and the expensive necessity of maintaining a supply of and frequently replacing aluminum wheels.

20

25

30

Steel, though stronger than aluminum, is also undesirably heavier and similarly subject to permanent deformation. It will also be appreciated, from a manufacturing standpoint, that steel and aluminum may, at times, be difficult to acquire, and can be relatively difficult and dangerous to work. Furthermore, delivery costs for the relatively heavy metal wheels can negatively impact profit margins.

Engineered polymer wheels are known in the art which provide an alternative to metal wheels in some applications, particularly high-performance bicycle, motorcycle, and race car applications, where their relatively light weight is highly desirable. Unfortunately, existing polymer wheels typically have little, if any, energy-absorbing flexibility. Thus, rather than deform, as metal wheels are wont to do, they often crack or fracture under similar stresses, being therefore suitable only for use on very lightweight vehicles or very smooth, managed race courses.

Existing wheels, whether constructed from a metal or a polymer, suffer from a number of additional disadvantages as well, including bead rings that are difficult to align and install; center sections in modular wheels that are unsealed or poorly sealed; and interior cavities wherein mud and debris become packed due to lack of or unsophisticated mechanisms for preventing such a build-up which could add undesired weight, unbalance the wheel, and prevent or hinder access to the mechanisms, such as lug bolts and nuts, coupling the wheel to the vehicle.

Due to the above-identified and other problems and disadvantages in the art, a need exists for an improved wheel.

SUMMARY OF THE INVENTION

The present invention provides a distinct advance in the art of wheels for vehicles. More particularly, the present invention provides a lightweight, energy-absorbing, flexible vehicle wheel constructed from an injection molded engineered polymer, such as, for example, a toughened nylon reinforced with up to approximately 50% of carbon fibers, glass fibers, or kevlar fibers, and operable to support a tire on a vehicle. The polymer wheel has, potentially, approximately twice the strength and half the weight of a similarly designed aluminum wheel, and may be embodied in both modular and one-piece configurations. The wheel has broad applicability to many types of vehicles and vehicular uses, and is particularly suited

for use on off-road vehicles and off-road racing vehicles that are subject to punishing driving conditions.

In a preferred first modular embodiment, the wheel broadly comprises an inboard wheel half; an outboard wheel half; a center section; a bead lock ring; and a mud plug. Preferably, at least the inboard wheel half and the outboard wheel half are constructed from the polymer. The inboard wheel half provides an inboard seal and support for the tire. The inboard wheel half presents an outwardly projecting bead flange or lip operable to contact and facilitate sealing thereagainst an inboard tire bead portion of the tire. The inboard wheel half also presents a circumferential tire locking rib in relatively close proximity to the bead flange and operable to facilitate retaining the tire on the wheel by restricting movement of the inboard tire bead.

The outboard wheel half provides an outboard seal and support for the tire. The outboard wheel half presents a bead lock surface operable to contact and facilitate sealing an outboard tire bead portion of the tire thereagainst. The bead lock surface presents a first portion of an alignment mechanism in the form of a plurality of slots.

The inboard and outboard wheel halves each include a plurality of elongated stiffening ribs. The length, thickness, and number of these stiffening ribs is a matter of design and application and will depend upon a desired balance between wheel stiffness and wheel flexibility. Furthermore, the inboard and outboard wheel halves are constructed so as to have varying cross-sectional thicknesses in order to further control stiffness and flexibility. Thus, the wheel is preferably thickest and therefore stiffest at or near its center section or center portion where the wheel is coupled with the vehicle, and is preferably thinnest and therefore most flexible at or near the inboard and outboard tire beads where cracking is most likely to occur in prior art polymer wheels and where deformation is most likely to occur in prior art metal wheels.

The center section provides a mechanism for coupling the inboard wheel half with the outboard wheel half, and for coupling the wheel with the vehicle. The center section may be constructed from any suitable material, such as, for example, aluminum, magnesium, or the polymer. O-rings, gaskets, or dynamic u-

cup seals are provided where the center section contacts the inboard and outboard wheels halves.

The bead lock ring is operable, in cooperation with the bead lock surface of the outboard wheel half, to facilitate sealing the outboard tire bead by clamping it therebetween. The bead lock ring is a substantially circular ring of the polymer material, and presents a second portion of the aforementioned alignment mechanism in the form of a plurality of projections which interlockingly cooperate with the plurality of slots to facilitate proper alignment of the bead lock surface with the bead lock ring. The projections also function to advantageously transfer loads during impacts, thereby further avoiding damage to the wheel.

The mud plug is operable to substantially prevent mud and debris from entering an interior cavity or area of the outboard wheel half and becoming stuck or packed therewithin. The mud plug may be adapted for use on the inboard wheel half as well by providing a center opening and slit for accommodating an axle of the wheel. Thus, the mud plug feature prevents a build-up of mud which would otherwise add undesirable weight and potentially unbalance the wheel, thereby causing undesirable vibrations. Furthermore, the mud plug ensures quick and convenient access to a valve stem inlet and to a plurality of lug bolts and nuts coupling the wheel with the vehicle. The mud plug removably couples with the wheel using quick release quarter-turn fasteners.

It will be appreciated by those with skill in the relevant arts, that the present invention provides a number of advantages over the prior art, including the stiffening ribs and varying cross-sectional thicknesses which minimize weight while substantially increasing wheel stiffness to prevent cracking or fracture failure due to driving stresses. This stiffness, however, is balanced with maintaining equally desirable energy-absorbing flexibility. Furthermore, the O-rings, gaskets, or dynamic u-cup seals interposed between the center section and both the inboard wheel half and the outboard wheel half provide a highly advantageous seal therebetween. Additionally, the interlocking alignment mechanism of the bead locking surface and bead ring facilitates easier and more convenient tire mounting and sealing. Additionally, the easily and conveniently removable mud plug provides an advantageous mechanism for preventing interior areas of the inboard and

outboard wheel halves from becoming packed with mud or debris, thereby preventing unwanted added weight and vibration while ensuring quick and easy access to the valve stem for inflating the tire and to the lug nuts or other mechanisms coupling the wheel to the vehicle.

5 These and other important features of the present invention are more fully described in the section titled DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT, below.

BRIEF DESCRIPTION OF THE DRAWINGS

10 A preferred embodiment of the present invention is described in detail below with reference to the attached drawing figures, wherein:

 FIG. 1 is an isometric view of a preferred first modular embodiment of the present invention;

15 FIG. 2 is an exploded isometric view of the embodiment shown in FIG. 1;

 FIG. 3 is an exploded isometric view of a center section component of the embodiment shown in FIG. 1;

 FIG. 4 is a fragmented sectional elevation view of a dynamic u-cup seal component of the present invention;

20 FIG. 5 is an exploded fragmented perspective view of an outboard wheel half component and a bead ring component of the embodiment shown in FIG. 1;

 FIG. 6 is a plan view of the embodiment shown in FIG. 1;

25 FIG. 7 is a sectional elevation view of the embodiment shown in FIG. 1 taken along line 1-1 of FIG. 6;

 FIG. 8 is an exploded isometric view of a mud plug component and the bead ring component of the embodiment shown in FIG. 1;

 FIG. 9 is an exploded isometric view of the mud plug component modified for inboard use;

30 FIG. 10 is an elevation view of a preferred second modular embodiment of the present invention; and

FIG. 11 is an isometric view of a preferred one-piece embodiment of the present invention.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

5 Referring to FIGs. 1-9, the present invention provides a lightweight, energy-absorbing, flexible wheel 12 constructed from an injection molded engineered polymer, and operable to support a tire on a vehicle. The wheel 12 has broad applicability to many types of vehicles and vehicular uses, and is particularly suited for use on off-road vehicles and off-road racing vehicles that are subject to punishing driving conditions. In a preferred modular embodiment, the wheel 12 broadly comprises an inboard wheel half 14; an outboard wheel half 16; a center section 18; a bead lock ring 20; and a mud plug 22.

10 A substantial portion of the wheel 12, particularly at least the inboard wheel half 14 and the outboard wheel half 16, are constructed from the polymer which is a toughened nylon reinforced with up to approximately 50% of carbon fibers, glass fibers, or kevlar fibers. A suitable polymer fitting this description is available, for example, from DuPont as "Zytel", product number CDV-805.

15 The inboard wheel half 14 provides an inboard seal and support for the tire. The inboard wheel half 14 is substantially cylindrical, presenting an outside end 26; an exterior surface 28; an interior surface 30; and an inside end 32. The outside end 26 presents an outwardly projecting bead flange or lip 34 operable to contact and facilitate sealing thereagainst an inboard bead portion of the tire. The exterior surface 28 presents a circumferential tire locking rib 36 in relatively close proximity to the bead flange 34 and operable to facilitate retaining the tire on the wheel 12 by restricting movement of the inboard bead portion. The interior surface 30 presents a plurality of stiffening ribs 38 having a maximum thickness near the inside end 32 and extending radially or longitudinally therefrom, generally following the contour of the interior surface 30 and tapering toward the outside end 26. The length, thickness, and number of the stiffening ribs 38 is a matter of design and application and will depend upon a desired balance between wheel stiffness and wheel flexibility. Alternatively or additionally, similar stiffening ribs (not shown) may be provided on the exterior surface 28 as well. The inside end 32 provides a contact

20

25

30

surface 40 operable to physically contact and couple with the center section 18. The contact surface 40 may be substantially flat or may provide interlocking contours, and, in either case, presents a plurality of bolt holes 42 extending completely therethrough. The inside end 32 also presents a plurality of cutouts 43
5 corresponding to and providing clearance for a mechanism, such as conventional lug bolts and nuts, for coupling the wheel 12 with the vehicle.

The outboard wheel half 16 provides an outboard seal and support for the tire. The outboard wheel half 16 is substantially cylindrical, presenting an inside end 44; an exterior surface 46; an interior surface 48; and an outside end 50. The
10 inside end 44 provides a contact surface (not shown, but substantially similar to the contact surface 40 of the inboard wheel half 14) operable to physically contact and couple with the center section 18. The contact surface may be substantially flat or may provide interlocking contours, and, in either case, presents a plurality of bolt
15 holes 52 extending completely therethrough. The inside end 44 also presents a plurality of cutouts 53 corresponding to and providing clearance for the lug bolts and nuts for coupling the wheel 12 with the vehicle. The exterior and interior surfaces 46,48 presents a plurality of stiffening ribs 54,55 that radiate axially outward from the inside end 44. The length, thickness, and number of the stiffening ribs 54,55 is a matter of design and application and will depend upon a desired balance between
20 wheel stiffness and wheel flexibility. The outside end 50 presents a first bead lock surface 58 operable to contact and facilitate sealing an outboard bead portion of the tire thereagainst. The first bead lock surface 58 presents a plurality of internally threaded bolt holes 60 and a plurality of slots 62. The slots 62 form a first portion of an alignment mechanism which is described in more detail below.

25 Referring particularly to FIGs. 6 and 7, the inboard wheel half 14 and the outboard wheel half 16 are constructed having varying cross-sectional thicknesses in order to control stiffness and flexibility characteristics of the wheel 12. The wheel halves 14,16 are preferably thickest at their inside ends 32,44 and generally diminish in thickness toward their outside ends 26,50, with the exception
30 of special features, such as for example, the bead flange 34 and the circumferential tire locking rib 36. Thus, the wheel 12 will be thickest and therefore stiffest at or near its center section 18 or center portion where the wheel 12 is coupled with the

vehicle, and will be thinnest and therefore most flexible near the inboard and outboard tire beads where cracking is most likely to occur in prior art polymer wheels and where deformation is most likely to occur in prior art metal wheels.

5 A conventional valve stem 84 is shown which allows the sealed tire to be inflated. As illustrated, the valve stem 84 extends completely through the outboard wheel half 16 to present an externally accessible air inlet 86 and a conduit 88 extending therefrom to an area corresponding to an interior area of the mounted tire.

10 Referring particularly to FIG. 3, the center section 18 provides a mechanism for coupling the inboard wheel half 14 with the outboard wheel half 16, and for coupling the wheel 12 with the vehicle. As illustrated, the center section 18 is constructed from billet aluminum. Extraneous material may be removed to save weight and cost. In other embodiments, the center section 18 may be constructed from any suitable material, including, for example, injection molded magnesium or the herein-described polymer.

15 The center section 18 presents an inboard center section contact surface 64 and an outboard center section contact surface 66. The inboard center section contact surface 64 corresponds to the contact surface 40 of the inside end 32 of the inboard wheel half 14, and will be correspondingly flat or contoured so as to securely interface therewith. Similarly, the outboard center section contact surface 66 corresponds to the contact surface of the inside end 44 of the outboard wheel half 16, and will be correspondingly flat or contoured so to securely interface therewith. The center section 18 includes first bolt holes 67 corresponding to the bolts holes 42 in the inboard wheel half 14 and the bolt holes 52 in the outboard wheel half 16. The center section 18 also provides lug bolt holes 68 for receiving the lug bolts for coupling the wheel 12 to the vehicle. Where the center section 18 is constructed from the polymer material, the lug bolts holes 68 will include compression limiting sleeves 70 operable to prevent stress on or damage to the polymer material due to tightening of the lug nuts thereon.

20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000
1005
1010
1015
1020
1025
1030
1035
1040
1045
1050
1055
1060
1065
1070
1075
1080
1085
1090
1095
1100
1105
1110
1115
1120
1125
1130
1135
1140
1145
1150
1155
1160
1165
1170
1175
1180
1185
1190
1195
1200
1205
1210
1215
1220
1225
1230
1235
1240
1245
1250
1255
1260
1265
1270
1275
1280
1285
1290
1295
1300
1305
1310
1315
1320
1325
1330
1335
1340
1345
1350
1355
1360
1365
1370
1375
1380
1385
1390
1395
1400
1405
1410
1415
1420
1425
1430
1435
1440
1445
1450
1455
1460
1465
1470
1475
1480
1485
1490
1495
1500
1505
1510
1515
1520
1525
1530
1535
1540
1545
1550
1555
1560
1565
1570
1575
1580
1585
1590
1595
1600
1605
1610
1615
1620
1625
1630
1635
1640
1645
1650
1655
1660
1665
1670
1675
1680
1685
1690
1695
1700
1705
1710
1715
1720
1725
1730
1735
1740
1745
1750
1755
1760
1765
1770
1775
1780
1785
1790
1795
1800
1805
1810
1815
1820
1825
1830
1835
1840
1845
1850
1855
1860
1865
1870
1875
1880
1885
1890
1895
1900
1905
1910
1915
1920
1925
1930
1935
1940
1945
1950
1955
1960
1965
1970
1975
1980
1985
1990
1995
2000
2005
2010
2015
2020
2025
2030
2035
2040
2045
2050
2055
2060
2065
2070
2075
2080
2085
2090
2095
2100
2105
2110
2115
2120
2125
2130
2135
2140
2145
2150
2155
2160
2165
2170
2175
2180
2185
2190
2195
2200
2205
2210
2215
2220
2225
2230
2235
2240
2245
2250
2255
2260
2265
2270
2275
2280
2285
2290
2295
2300
2305
2310
2315
2320
2325
2330
2335
2340
2345
2350
2355
2360
2365
2370
2375
2380
2385
2390
2395
2400
2405
2410
2415
2420
2425
2430
2435
2440
2445
2450
2455
2460
2465
2470
2475
2480
2485
2490
2495
2500
2505
2510
2515
2520
2525
2530
2535
2540
2545
2550
2555
2560
2565
2570
2575
2580
2585
2590
2595
2600
2605
2610
2615
2620
2625
2630
2635
2640
2645
2650
2655
2660
2665
2670
2675
2680
2685
2690
2695
2700
2705
2710
2715
2720
2725
2730
2735
2740
2745
2750
2755
2760
2765
2770
2775
2780
2785
2790
2795
2800
2805
2810
2815
2820
2825
2830
2835
2840
2845
2850
2855
2860
2865
2870
2875
2880
2885
2890
2895
2900
2905
2910
2915
2920
2925
2930
2935
2940
2945
2950
2955
2960
2965
2970
2975
2980
2985
2990
2995
3000
3005
3010
3015
3020
3025
3030
3035
3040
3045
3050
3055
3060
3065
3070
3075
3080
3085
3090
3095
3100
3105
3110
3115
3120
3125
3130
3135
3140
3145
3150
3155
3160
3165
3170
3175
3180
3185
3190
3195
3200
3205
3210
3215
3220
3225
3230
3235
3240
3245
3250
3255
3260
3265
3270
3275
3280
3285
3290
3295
3300
3305
3310
3315
3320
3325
3330
3335
3340
3345
3350
3355
3360
3365
3370
3375
3380
3385
3390
3395
3400
3405
3410
3415
3420
3425
3430
3435
3440
3445
3450
3455
3460
3465
3470
3475
3480
3485
3490
3495
3500
3505
3510
3515
3520
3525
3530
3535
3540
3545
3550
3555
3560
3565
3570
3575
3580
3585
3590
3595
3600
3605
3610
3615
3620
3625
3630
3635
3640
3645
3650
3655
3660
3665
3670
3675
3680
3685
3690
3695
3700
3705
3710
3715
3720
3725
3730
3735
3740
3745
3750
3755
3760
3765
3770
3775
3780
3785
3790
3795
3800
3805
3810
3815
3820
3825
3830
3835
3840
3845
3850
3855
3860
3865
3870
3875
3880
3885
3890
3895
3900
3905
3910
3915
3920
3925
3930
3935
3940
3945
3950
3955
3960
3965
3970
3975
3980
3985
3990
3995
4000
4005
4010
4015
4020
4025
4030
4035
4040
4045
4050
4055
4060
4065
4070
4075
4080
4085
4090
4095
4100
4105
4110
4115
4120
4125
4130
4135
4140
4145
4150
4155
4160
4165
4170
4175
4180
4185
4190
4195
4200
4205
4210
4215
4220
4225
4230
4235
4240
4245
4250
4255
4260
4265
4270
4275
4280
4285
4290
4295
4300
4305
4310
4315
4320
4325
4330
4335
4340
4345
4350
4355
4360
4365
4370
4375
4380
4385
4390
4395
4400
4405
4410
4415
4420
4425
4430
4435
4440
4445
4450
4455
4460
4465
4470
4475
4480
4485
4490
4495
4500
4505
4510
4515
4520
4525
4530
4535
4540
4545
4550
4555
4560
4565
4570
4575
4580
4585
4590
4595
4600
4605
4610
4615
4620
4625
4630
4635
4640
4645
4650
4655
4660
4665
4670
4675
4680
4685
4690
4695
4700
4705
4710
4715
4720
4725
4730
4735
4740
4745
4750
4755
4760
4765
4770
4775
4780
4785
4790
4795
4800
4805
4810
4815
4820
4825
4830
4835
4840
4845
4850
4855
4860
4865
4870
4875
4880
4885
4890
4895
4900
4905
4910
4915
4920
4925
4930
4935
4940
4945
4950
4955
4960
4965
4970
4975
4980
4985
4990
4995
5000
5005
5010
5015
5020
5025
5030
5035
5040
5045
5050
5055
5060
5065
5070
5075
5080
5085
5090
5095
5100
5105
5110
5115
5120
5125
5130
5135
5140
5145
5150
5155
5160
5165
5170
5175
5180
5185
5190
5195
5200
5205
5210
5215
5220
5225
5230
5235
5240
5245
5250
5255
5260
5265
5270
5275
5280
5285
5290
5295
5300
5305
5310
5315
5320
5325
5330
5335
5340
5345
5350
5355
5360
5365
5370
5375
5380
5385
5390
5395
5400
5405
5410
5415
5420
5425
5430
5435
5440
5445
5450
5455
5460
5465
5470
5475
5480
5485
5490
5495
5500
5505
5510
5515
5520
5525
5530
5535
5540
5545
5550
5555
5560
5565
5570
5575
5580
5585
5590
5595
5600
5605
5610
5615
5620
5625
5630
5635
5640
5645
5650
5655
5660
5665
5670
5675
5680
5685
5690
5695
5700
5705
5710
5715
5720
5725
5730
5735
5740
5745
5750
5755
5760
5765
5770
5775
5780
5785
5790
5795
5800
5805
5810
5815
5820
5825
5830
5835
5840
5845
5850
5855
5860
5865
5870
5875
5880
5885
5890
5895
5900
5905
5910
5915
5920
5925
5930
5935
5940
5945
5950
5955
5960
5965
5970
5975
5980
5985
5990
5995
6000
6005
6010
6015
6020
6025
6030
6035
6040
6045
6050
6055
6060
6065
6070
6075
6080
6085
6090
6095
6100
6105
6110
6115
6120
6125
6130
6135
6140
6145
6150
6155
6160
6165
6170
6175
6180
6185
6190
6195
6200
6205
6210
6215
6220
6225
6230
6235
6240
6245
6250
6255
6260
6265
6270
6275
6280
6285
6290
6295
6300
6305
6310
6315
6320
6325
6330
6335
6340
6345
6350
6355
6360
6365
6370
6375
6380
6385
6390
6395
6400
6405
6410
6415
6420
6425
6430
6435
6440
6445
6450
6455
6460
6465
6470
6475
6480
6485
6490
6495
6500
6505
6510
6515
6520
6525
6530
6535
6540
6545
6550
6555
6560
6565
6570
6575
6580
6585
6590
6595
6600
6605
6610
6615
6620
6625
6630
6635
6640
6645
6650
6655
6660
6665
6670
6675
6680
6685
6690
6695
6700
6705
6710
6715
6720
6725
6730
6735
6740
6745
6750
6755
6760
6765
6770
6775
6780
6785
6790
6795
6800
6805
6810
6815
6820
6825
6830
6835
6840
6845
6850
6855
6860
6865
6870
6875
6880
6885
6890
6895
6900
6905
6910
6915
6920
6925
6930
6935
6940
6945
6950
6955
6960
6965
6970
6975
6980
6985
6990
6995
7000
7005
7010
7015
7020
7025
7030
7035
7040
7045
7050
7055
7060
7065
7070
7075
7080
7085
7090
7095
7100
7105
7110
7115
7120
7125
7130
7135
7140
7145
7150
7155
7160
7165
7170
7175
7180
7185
7190
7195
7200
7205
7210
7215
7220
7225
7230
7235
7240
7245
7250
7255
7260
7265
7270
7275
7280
7285
7290
7295
7300
7305
7310
7315
7320
7325
7330
7335
7340
7345
7350
7355
7360
7365
7370
7375
7380
7385
7390
7395
7400
7405
7410
7415
7420
7425
7430
7435
7440
7445
7450
7455
7460
7465
7470
7475
7480
7485
7490
7495
7500
7505
7510
7515
7520
7525
7530
7535
7540
7545
7550
7555
7560
7565
7570
7575
7580
7585
7590
7595
7600
7605
7610
7615
7620
7625
7630
7635
7640
7645
7650
7655
7660
7665
7670
7675
7680
7685
7690
7695
7700
7705
7710
7715
7720
7725
7730
7735
7740
7745
7750
7755
7760
7765
7770
7775
7780
7785
7790
7795
7800
7805
7810
7815
7820
7825
7830
7835
7840
7845
7850
7855
7860
7865
7870
7875
7880
7885
7890
7895
7900
7905
7910
7915
7920
7925
7930
7935
7940
7945
7950
7955
7960
7965
7970
7975
7980
7985
7990
7995
8000
8005
8010
8015
8020
8025
8030
8035
8040
8045
8050
8055
8060
8065
8070
8075
8080
8085
8090
8095
8100
8105
8110
8115
8120
8125
8130
8135
8140
8145
8150
8155
8160
8165
8170
8175
8180
8185
8190
8195
8200
8205
8210
8215
8220
8225
8230
8235
8240
8245
8250
8255
8260
8265
8270
8275
8280
8285
8290
8295
8300
8305
8310
8315
8320
8325
8330
8335
8340
8345
8350
8355
8360
8365
8370
8375
8380
8385
8390
8395
8400
8405
8410
8415
8420
8425
8430
8435
8440
8445
8450
8455
8460
8465
8470
8475
8480
8485
8490
8495
8500
8505
8510
8515
8520
8525
8530
8535
8540
8545
8550
8555
8560
8565
8570
8575
8580
8585
8590
8595
8600
8605
8610
8615
8620
8625
8630
8635
8640
8645
8650
8655
8660
8665
8670
8675
8680
8685
8690
8695
8700
8705
8710
8715
8720
8725
8730
8735
8740
8745
8750
8755
8760
8765
8770
8775
8780
8785
8790
8795
8800
8805
8810
8815
8820
8825
8830
8835
8840
8845
8850
8855
8860
8865
8870
8875
8880
8885
8890
8895
8900
8905
8910
8915
8920
8925
8930
8935
8940
8945
8950
8955
8960
8965
8970
8975
8980
8985
8990
8995
9000
9005
9010
9015
9020
9025
9030
9035
9040
9045
9050
9055
9060
9065
9070
9075
9080
9085
9090
9095
9100
9105
9110
9115
9120
9125
9130
9135
9140
9145
9150
9155
9160
9165
9170
9175
9180
9185
9190
9195
9200
9205
9210
9215
9220
9225
9230
9235
9240
9245
9250
9255
9260
9265
9270
9275
9280
9285
9290
9295
9300
9305
9310
9315
9320
9325
9330
9335
9340
9345
9350
9355
9360
9365
9370
9375
9380
9385
9390
9395
9400
9405
9410
9415
9420
9425
9430
9435
9440
9445
9450
9455
9460
9465
9470
9475
9480
9485
9490
9495
9500
9505
9510
9515
9520
9525
9530
9535
9540
9545
9550
9555
9560
9565
9570
9575
9580
9585
9590
9595
9600
9605
9610
9615
9620
9625
9630
9635
9640
9645
9650
9655
9660
9665
9670
9675
9680
9685
9690
9695
9700
9705
9710
9715
9720
9725
9730
9735
9740
9745
9750
9755
9760
9765
9770
9775
9780
9785
9790
9795
9800
9805
9810
9815
9820
9825
9830
9835
9840
9845
9850
9855
9860
9865
9870
9875
9880
9885
9890
9895
9900
9905
9910
9915
9920
9925
9930
9935
9940
9945

particularly to FIG. 4, which shows a cross-sectional view of a typical dynamic u-cup seal 73, the dynamic u-cup seal 73 is preferred in some applications, particularly where the wheel 12 could flex sufficiently to cause the O-ring 71 to unload and unseal. The dynamic u-cup seal 73 is a conventional sealing mechanism available from a variety of sources. Where the gasket 70 is used, bolt holes 72 and cutouts 73 are provided therein which correspond, respectively, to the bolt holes 67 and lug bolt holes 68 in the center section 18. Where the O-ring 71 or the dynamic u-cup seal 73 is used, a groove 72 is provided in the contact surface 64,66 of the center section 18 for receiving such.

Referring particularly to FIG 5, the bead lock ring 20 is a substantially circular ring of the engineered polymer material presenting an outer surface 76 and an inner surface 78, and a plurality of bolt holes 80 extending completely therethrough. The bolt holes 80 are preferably counter-sunk into the outer surface 76 so that the bolt heads do not protrude therepast. The inner surface 78 of the bead lock ring 20 presents a second bead lock surface 79 and a taper 81. The second bead lock surface 79 presents projections 82 corresponding to and operable to be received within and interlockingly cooperate with the slots 72 of the first bead lock surface 58 of the outside end 60 of the outboard wheel half 16. When the projections 82 are received within the slots 72, the bolt holes 60,80 will be properly aligned. Thus, the projections 82 form a second portion of the alignment mechanism mentioned above. The taper 81 facilitates properly aligning the outboard tire bead between the first and second bead locking surfaces 58,79.

Referring particularly to FIG. 8, the mud plug 22 is operable when installed to substantially prevent mud and debris from entering the interior cavity or area of the outboard wheel half 16 and becoming stuck or packed therein. Thus, the mud plug 22 prevents a build-up of mud inside the wheel 12 which would add undesirable weight and might unbalance the wheel 12, thereby causing undesirable vibrations. Furthermore, the mud plug 22 ensures quick and convenient access to the valve stem inlet 86 and to a plurality of lug bolts and nuts coupling the wheel 12 with the vehicle.

In a preferred embodiment, the mud plug 22 includes a mud shield 86, and a plurality of mounting tabs 88. The mud shield 86 is preferably round so as to

substantially cap or cover the interior area or cavity of the outboard wheel half 16. In a preferred embodiment, the mud shield 86 is constructed from a polycarbonate of between approximately 1/32 and 1/8 inch thickness. The mounting tabs 88 are removably secured between the first and second bead lock surfaces 58,79, and are operable to removably couple with the mud shield 86 using conventional quick release, quarter-turn fasteners 89. A retainer 90 is provided for each of the fasteners 89 to facilitate retaining them with the mud shield 86 when the mud shield 86 is removed from the mounting tabs 88. In a preferred embodiment, particular bolt holes 92 in the second bead lock surface 79 of the bead ring 20 have relief contouring 94 so to receive the mounting tabs 88 without interfering with the cooperative interaction between the first and second bead lock surfaces 68,79.

Referring particularly to FIG. 9, an embodiment of the mud plug 122 is shown adapted for use on the inboard wheel half 14, wherein a center opening 123 and slit 125 in the mud shield 186 is provided to accommodate a vehicle axle. The center opening 123 is sized so as to allow the axle to pass therethrough. The slit 125 allows the mud shield 186 to be opened to allow the axle to pass through to the center opening 123. Other than such accommodation of the axle, this inboard-adapted embodiment of the mud plug functions in a manner identical to the outboard embodiment described above.

Referring also to FIG. 10, a preferred second modular embodiment of the wheel 112 is shown which is substantially similar to the preferred first embodiment described above, but in which the inboard wheel half 114 is substantially elongated and similar or identical to the outboard wheel half 116. Furthermore, the wheel 112 is shown comprising two similar or identical bead rings, including an inboard bead ring 120, associated with the inboard wheel half 114, and an outboard bead ring 121, associated with the outboard wheel half 116, thereby eliminating the bead flange 34 and the circumferential tire locking rib 36 of the preferred first modular embodiment.

Referring also to FIG. 11, in a preferred one-piece embodiment, the wheel 212 is similar in overall design and construction to the preferred modular embodiments described above. In the one-piece wheel 212, however, the distinct center section 14 is eliminated because the wheel 212 is manufactured as a single

unit comprising an integral inboard portion 214 and an integral outboard portion 216 rather than the separable halves 14,16 of the modular embodiments. As illustrated, the wheel 212 includes no bead ring 20, but includes instead an inboard bead flange 234 and outboard bead flange 235.

Referring again to the wheel 12 of the first preferred modular embodiment, in exemplary use and operation the modular wheel components are initially provided in a disassembled state. During assembly, if gaskets 70 are used, the gaskets 70 are set upon the center section contact surfaces 64,66 such that the cutouts 73 of the gaskets 70 properly align with the lug bolts holes 68 of the center section 18. If O-rings 71 or dynamic u-cup seals 73 are used, they are installed by pressing them into the grooves 72 provided in the center section contact surfaces 64,66. The inboard wheel half 14 and the outboard wheel half 16 are then coupled with the center section 18 by bringing the contact surface 40 of the inside end 32 of the inboard wheel half 14 into contact with the inboard center section contact surface 64; bringing the contact surface (not shown) of the inside end 44 of the outboard wheel half 16 into contact with the outboard center section contact surface 66; aligning the bolt holes 42,67,52; passing bolts through the bolt holes 42,67,52 in the direction of the inboard wheel half 14; and applying nuts on the inboard ends of the bolts. The bolts are then torqued to specifications appropriate to the wheel design and application.

The tire is then applied to the wheel 12 by pushing or prying the tire thereupon so that the inboard tire bead is positioned between the bead flange or lip 34 and the circumferential tire locking rib 36 of the inboard wheel half 14, and the outboard bead of the tire is positioned on the first bead lock surface 58 of the outboard wheel half 16. The bead lock ring 20 is then placed upon the bead lock surface 58 such that the projections 82 align with and are received into the slots 62, thereby automatically aligning the bolt holes 60,80. The taper 81 facilitates properly aligning the tire between the first and second bead lock surfaces 58,79. Thus, the outboard bead of the tire is trapped or sandwiched between the first and second bead lock surfaces 58,79. Bolts are then threaded into the bolt holes 60,80 and tightened to seal the tire. The tire is then inflated using the valve stem 84. The

wheel 12 may thereafter be conventionally mounted to the vehicle using, for example, the lug bolts and nuts or some other coupling mechanism.

If use of the mud plug 22 is desired, three bolts associated with the specially contoured bolt holes 92 of the bead ring 20 are removed; the mounting tabs 88 are inserted therein; and the bolts replaced in the bolt holes 92, thereby clamping the mounting tabs 88 between the first and second bead lock surfaces 58,79. The mud shield 86 may then be installed and removed, as desired, without removing the mounting tabs 88, by using the quick release quarter-turn fasteners 89. When the mud shield is removed 86, the retainers 90 retain the fasteners 89 thereupon to prevent loss.

For the preceding description, it will be appreciated that the present invention provides a lightweight, energy-absorbing, flexible vehicle wheel constructed from an injection molded engineered polymer, such as, for example, a toughened nylon reinforced with up to approximately 50% of carbon fibers, glass fibers, or kevlar fibers. The polymer wheel has, potentially, twice the strength and half the weight of aluminum wheels of similar design, and may be embodied in modular or one-piece designs. The wheel has general applicability to many types of vehicles and vehicular uses, and is particularly suited for use on off-road vehicles and off-road racing vehicles that are subject to punishing driving conditions. The wheel provides a number of advantages over existing wheels, including ribs and varying cross-sectional thicknesses that substantially increase wheel stiffness, thereby helping to prevent cracking or fracture failure due to driving stresses. This stiffness, however, is balanced with maintaining equally desirable energy-absorbing abilities and flexibility qualities. Furthermore, the gaskets, O-rings, or dynamic u-cup seals interposed between the center section and both the inboard and outboard wheel halves provide a highly advantageous seal therebetween. Additionally, the interlocking alignment mechanism of the first and second bead locking surfaces facilitate easier and more convenient tire mounting and sealing. Additionally, the easily and conveniently removable mud plug provides an advantageous mechanism for preventing the interior area or cavity of the inboard and outboard wheel halves from becoming packed with mud or debris, thereby preventing a build-up of weight-adding mud which might unbalance the wheel and cause undesirable vibration,

while ensuring quick and easy access to the valve stem for inflating the tire and to the lug nuts or other mechanism coupling the wheel to the vehicle.

Although the invention has been described with reference to the preferred embodiments illustrated in the attached drawings, it is noted that equivalents may be employed and substitutions made herein without departing from the scope of the invention as recited in the claims. For example, the wheel's dimensions, including radius and depth will vary depending on each particular contemplated application. Furthermore, as will be appreciated from the various described embodiments, the wheel may include two bead flanges and no bead locking rings; two bead locking rings and no beads flanges; or one bead flange and one bead locking ring.

Having thus described the preferred embodiment of the invention, what is claimed as new and desired to be protected by Letters Patent includes the following: